

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
7 July 2005 (07.07.2005)

PCT

(10) International Publication Number
WO 2005/061207 A1

(51) International Patent Classification⁷: **B29C 47/38**

(21) International Application Number:

PCT/IB2004/052850

(74) Agent: **VIEIRA PEREIRA FERREIRA, Maria, Silvina; CLARKE, MODET & Cº, Rua Castilho N.º 50 - 5º, P-1269-163 Lisboa (PT).**

(22) International Filing Date:

17 December 2004 (17.12.2004)

(81) **Designated States** (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(25) Filing Language:

English

(26) Publication Language:

English


(30) Priority Data:

103053 18 December 2003 (18.12.2003) PT

(84) **Designated States** (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: MICRO-EXTRUSION LINE



(57) **Abstract:** The invention refers to a micro-extrusion line that comprises a single screw (2) micro-extruder (1), a die (7), a cooling bath (17) and a haul-off (19), which together enables the manufacture of extruded profiles from small amounts of raw material. The rotation of the micro-extruder screw, together with the high temperatures created by the heater bands, produces the conveying, melting, mixing and pumping of the material through the die. The extrudate is cooled down in a bath containing a cooling liquid and wound in a coil (19), which has a linear speed higher than that of the extrusion, thus enabling the control of the extrudate cross-section.

WO 2005/061207 A1

**Declaration under Rule 4.17:**

— *of inventorship (Rule 4.17(iv)) for US only*

Published:

— *with international search report*
— *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.